



Main Street  
Creighton, 3263  
P.O Box 62  
Creighton 3263  
Phone: +27 39 833 1038  
Fax: +27 39 833 1179  
Email: mailbox@ndz.gov.za  
www.ndz.gov.za

**A Better Place for All**

**ADDENDUM FOR SUPPLY AND DELIVERY OF FIRE FIGHTING  
EQUIPMENT FOR A PERIOD OF THREE (3) YEARS  
BID NO: COMM-B035/24/25**

**Date: 06/12/2024**

The addendum serves to correct page (9 -12) specification and Pricing schedule page (20 – 23) and extend the closing date.

1. On page (9 –12) to correct item list for the specification we had duplications and specification was not clear for service providers (see attached corrected page and corrected pricing schedule 20-23)

**See below extended date:**

PROJECT NAME	CONTRACT NO.	EXTENDED DATE AND TIME FOR CLOSING
SUPPLY AND DELIVERY OF FIRE FIGHTING EQUIPMENT FOR A PERIOD OF THREE (3) YEARS	COMM-B035/24/25	16 <sup>th</sup> January 2025 @12h00

**RECOMMENDED BY:**

  
**MISS N. HOLIWE  
SCM MANAGER  
MANAGER**

**APPROVED BY:**

  
**MR. N.C. VEZI  
MUNICIPAL**

**I acknowledge receipt of this Addendum No.1**

Name:.....

Signature:.....

Date:.....

Name of Tenderer (Company Name):.....

## DETAILED SPECIFICATION

### FIRE FIGHTING EQUIPMENT SPECIFICATION CONTRACT

Item description
1. Suction spanner to fit 100mm Suction Hose
2. Metal suction Strainer - 100mm
3. Strainer basket 125 mm
4. Bolt cutter 650mm
5. Pick head fireman's axe with fiberglass handle 900mm
6. Shovel flat nose
7. Spade
8. Salvage sheet 4x4 meters
9. Four-pound hammer
10. Toolbox 57 piece complete with equipment spanners, screw drivers and sockets (medium set with lifetime guarantee)
11. Seatbelt cutter / rescue knife
12. Fire Hydrant adapter - 65mm BIC -1.2M Aluminum
13. Hydrant key and bar 1.2 m
14. Halligan tool with steel handle ( medium)
15. Crow bar 900mm
16. Basket stretcher
17. Low Expansion Foam Branch with inline inductor and pick up tube
18. GP line with bag -30metres
19. Dividing breech 65mm
20. Nozzle pistol grip adjustable with BIC coupling (115 - 475 liters per minute)
21. Drip torch (metal) 5L
22. Reflective traffic cones
23. Flat head axe (medium)
24. Fire man's axe with steel handle (medium)
25. Ceiling hook <ul style="list-style-type: none"><li>• 2.1 meter length</li><li>• Non-slip grip holds</li><li>• High- strength 40mm diameter fiberglass pole</li><li>• Steel head</li></ul>
26. Rubber firefighting heavy duty hose with BIC couplings 65mmx30m(with male and female couplings)
27. Rubber firefighting heavy duty hose with BIC couplings 28mmx30m(with male and female couplings)
29. Window punch
30. Complete BAA jump bag fully equipped
31. Vehicle Extrication Stabilization Set (Chock Set), Must be: <ul style="list-style-type: none"><li>• durable and shatterproof</li><li>• oil- and chemical resistant</li><li>• max load capacity up to 110kg/cm<sup>3</sup></li><li>• made of recycled PE</li></ul> Must include the following: <ul style="list-style-type: none"><li>• 4 x Chocks</li><li>• 4 x Wedges</li><li>• 2 x Different Blocks</li></ul>

<ul style="list-style-type: none"> <li>• Transport Bag</li> </ul>
32. Firefighter hand held torches (heavy duty ) Must have 300 L Li-ion rechargeable batteries Must be able to have both floodlight and spotlight capabilities
33. Hydrant wheel key (T-key)
34. High pressure cleaner 150 bar industrial use
35. Dividing breech – 65mm
36. Collecting breech – 65mm
37. Portable foam injection and application system
38. Hand controlled firefighting nozzle with building foam attachment
39. Medium expansion Foam Branch with inline inductor and pick up tube
40. 2400 L/M Oscillating Ground Monitor
41. Class A Foam minimum 25liter
42. Class B Foam minimum 25liter
43. Emergency Light Set – Battery Operated – with 1,8m tripod stand to meet NFPA 1971-8, must be re-chargeable with integrated rechargeable li-ion battery, waterproof and dustproof– IP-X7, must include AC & DC charging cords, must be supplied in moulded case.
44. Wheeled generator 5.5kVa, Fuel type: Petrol, Manual/Electronic Ignition system
45. 10 kg Sledgehammer
46. 45cm PPV Fan – Dimensions - 6745MM X 554MM X 490MM with direct drive Petrol Motor
47. Drip torch <ul style="list-style-type: none"> <li>• Tank- cold drawn steel welded 4.5 litres</li> <li>• Extension wand – steel tubing, steel nozzle</li> <li>• Burner- Fiberglass packed replaceable bolt on</li> </ul>
48. DCP fire extinguisher (9kg)
49. Co2 fire extinguisher (5kg)
50. Foam fire extinguisher (9kg)
51. DCP fire extinguisher (4.5kg)
52. Extension ladder aluminium minimum 6meters extension
53. Hydraulic rescue Cutter Heavy duty - battery operated: Batteries must be Lithium-ion type, 28V with high output with minimum 5,5Ah. The tool must be supplied with a battery and a 220V and 12/24V Vehicle Charger. <ol style="list-style-type: none"> <li>Construction must be lightweight and slim</li> <li>The rescue cutter must use smooth cut technology for smooth, low-stress and safe cutting</li> <li>The cutter blades must be high-strength, forged lightweight with optimised blade geometry for maximum safety with low weight</li> <li>It must have a handle manufactured from glass fibre reinforced plastic that can rotate 360° for use in tight spaces</li> <li>The rescue cutter must have blade inserts for blade protection and easy replacement</li> <li>The tool must have a maximum opening size of 187mm at the tips</li> <li>The tool must comply with EN Class BC187K-21,9</li> <li>The tool must comply with NFPA Class A8-B9-C7-D9-E9-F4</li> <li>EN cutting performance (EN 13204) 1K-2K-3K-4K-5K</li> <li>The tool with battery included must weigh maximum 19,1 kg</li> <li>Dimensions must not exceed: <ol style="list-style-type: none"> <li>1. Length: approximately 920mm</li> <li>2. Width: approximately 236mm</li> <li>3. Height: approximately 241 mm</li> </ol> </li> </ol>

54. Hydraulic Rescue Spreader heavy duty - battery operated:  
Batteries must be Lithium-ion type, 28V with high output with minimum 5,5Ah. The tool must be supplied with a battery and a 220V and 12/24V Vehicle Charger.

- a. Construction must be lightweight and slim
- b. Tips must have interior and exterior spikes for extra grip
- c. It must have a handle manufactured from glass fibre reinforced plastic that can rotate 360° for use in tight spaces
- d. It must have a spreading width of at least 805mm and a pulling width of at least 680mm
- e. Spreading force in the working area must be 50 - 501kN
- f. Maximum squeezing force must be at least 144kN and pulling force must be at least 67kN
- g. Must comply with EN Class BS50/805-20.9
- h. The tool with battery included must weigh maximum 20.9 kg
- i. Dimensions must not exceed:
  4. Length: approximately 1015mm
  5. Width: approximately 282mm
  6. Height: approximately 241 mm

55. Telescopic Hydraulic Rescue Ram heavy duty- battery operated:  
Batteries must be Lithium-ion type, 28V with high output with minimum 5,5Ah. The tool must be supplied with a battery and a 220V and 12/24V Vehicle Charger.

- a. Construction must be lightweight and slim
- b. The rescue ram must be telescopic with a maximum length of 1500mm
- c. The rescue ram must have integrated remaining length indication on the piston rod that must be easily visible
- d. The first stage pushing force must be maximum 108kN and the second stage pushing force must be maximum 62kN
- e. The closed length of the ram must be maximum 700mm and the extended length must be maximum 1500mm
- f. Must comply with EN Class: TR108/428-62/372-22,7-E-I
- g. Piston stroke for the first and second stages must be at least 428mm/372mm
- h. The tool with battery included must weigh maximum 22.7 kg
- i. Dimensions must not exceed:
  7. Length closed: approximately 700mm
  8. Width : approximately 134mm
  9. Height: approximately 365 mm

56. High lift jack (heavy duty) with minimum 3Ton Lifting Capacity

57. 8 Bar Lifting Bag Set with Controllers:

Set must consist of the following:

- 1 x 8 Bar Lifting bag – 230mm x 23mm x 25mm; Max lifting capacity of 2.7T;
- 1 x 8 Bar Lifting Bag – 380mm x 380mm x 25mm; Max Lifting capacity of 10.1T;
- 2 x \* Bar Flat Lifting Bags – 610mm x 610mm x 25mm – Max Lifting capacity of 25.2T;
- 1 x 200/300 Bar Pressure Reducer
- 2 x 25m inflation hose (1 x red & 1 x yellow)
- 1 x Double Controller

58a. SCBA complete set

- FPS7000 mask

<ul style="list-style-type: none"> <li>• Steel cylinder</li> <li>• PSS4000 back plate</li> </ul>
58b. SCBA complete set <ul style="list-style-type: none"> <li>• FPS7000 mask</li> <li>• Composite cylinder</li> <li>• PSS4000 back plate</li> </ul>
59. Spare cylinder (300 bar) steel
60. Spare cylinder (300 bar) composite
61. Bakkie sakkie 600 litres plastic tank with steel frame <ul style="list-style-type: none"> <li>• FP60T GX 160 petrol</li> <li>• 20mm x 60 meter rubber hose</li> <li>• Adjustable nozzle</li> <li>Chains and adjustment</li> </ul>
62. Stand pipe (aluminum) <ul style="list-style-type: none"> <li>• Inlet-bayonet connection (large)</li> <li>• Outlet – 65mm female</li> </ul>
63. Stand pipe –(aluminum) <ul style="list-style-type: none"> <li>• Inlet-V –tred</li> <li>• Outlet- 65mm female</li> </ul>
64. Hazmat plastic shovel
65. Big bass broom <ul style="list-style-type: none"> <li>• Wooden handle</li> <li>• 1.2 meter</li> <li>• Broom width 0.6m</li> </ul>
66. Heavy duty chain 20 meters
67. Jerry can 10 liters metal
68. Basket Stretcher aluminum /Stainless Steel with lifting bridles for helicopter rescue
69. Car wash flexible hose <ul style="list-style-type: none"> <li>• Tap connector</li> <li>• Adjustable nozzle branch</li> <li>• 15mm x 30meters</li> </ul>
70. Heavy duty electric extension cord <ul style="list-style-type: none"> <li>• With frame with 3x sockets (40 meters)</li> </ul>
71. Jumper cables (heavy duty) min 3000amp capacity
72. Scoop stretcher – Aluminum
73. Sked stretcher
74. Spinal board – Plastic with spider harness and head blocks
75. SCBA compressor (electric) – 300 Bar
76. Lawnmower minimum 190cc push petrol powered lawn mower, Cutting width: 48 cm, Minimum cutting height: 2 cm. minimum power: 3400 W, a powder coated steel chassis and heavy duty wheels for use in large gardens
77. Fire beater: <ul style="list-style-type: none"> <li>• with wooden handle</li> <li>• 1.5m</li> <li>• with rubber flap</li> <li>• Length 0.9m, width 0.4m.</li> </ul>
78. Squeege
79. Crow bar minimum 750mm x 19mm
80. Bobojan wrench spanner minimum 30cm
81. Fire drag rake – clawed with wooden handle
82. Battery operated reciprocating saw with battery and charger in carry case
83. Foil Mylar thermal blanket
84. Pick up tube with inline inductor

85. Knapsack backpack tank capacity 20liters
86. Chisel 3 Piece Cold Chisel Set
87. Folding ladder aluminum multipurpose minimum 3m extension

## PRICING SCHEDULE

### FIRE FIGHTING EQUIPMENT SPECIFICATION CONTRACT

Item description	Quantity	Rate	Total
1. Suction spanner to fit 100mm Suction Hose			
2. Metal suction Strainer - 100mm			
3. Strainer basket 125 mm			
4. Bolt cutter 650mm			
5. Pick head fireman's axe with fiberglass handle 900mm			
6. Shovel flat nose			
7. Spade			
8. Salvage sheet 4x4 meters			
9. Four-pound hammer			
10. Toolbox 57 piece complete with equipment spanners, screw drivers and sockets (medium set with lifetime guarantee)			
11. Seatbelt cutter / rescue knife			
12. Fire Hydrant adapter - 65mm BIC -1.2M Aluminum			
13. Hydrant key and bar 1.2 m			
14. Halligan tool with steel handle ( medium)			
15. Crow bar 900mm			
16. Basket stretcher			
17. Low Expansion Foam Branch with inline inductor and pick up tube			
18. GP line with bag -30metres			
19. Dividing breech 65mm			
20. Nozzle pistol grip adjustable with BIC coupling (115 - 475 liters per minute)			
21. Drip torch (metal) 5L			
22. Reflective traffic cones			
23. Flat head axe (medium)			
24. Fire man's axe with steel handle (medium)			
25. Ceiling hook <ul style="list-style-type: none"> <li>• 2.1 meter length</li> <li>• Non-slip grip holds</li> <li>• High- strength 40mm diameter fiberglass pole</li> <li>• Steel head</li> </ul>			
26. Rubber firefighting heavy duty hose with BIC couplings 65mmx30m(with male and female couplings)			
27. Rubber firefighting heavy duty hose with BIC couplings 28mmx30m(with male and female couplings)			
29. Window punch			
30. Complete BAA jump bag fully equipped			
31. Vehicle Extrication Stabilization Set (Chock Set), Must be:			

<ul style="list-style-type: none"> <li>• durable and shatterproof</li> <li>• oil- and chemical resistant</li> <li>• max load capacity up to 110kg/cm<sup>3</sup></li> <li>• made of recycled PE</li> </ul> <p>Must include the following:</p> <ul style="list-style-type: none"> <li>• 4 x Chocks</li> <li>• 4 x Wedges</li> <li>• 2 x Different Blocks</li> <li>• Transport Bag</li> </ul>			
32. Firefighter hand held torches (heavy duty ) Must have 300 L Li-ion rechargeable batteries Must be able to have both floodlight and spotlight capabilities			
33. Hydrant wheel key (T-key)			
34. High pressure cleaner 150 bar industrial use			
35. Dividing breech – 65mm			
36. Collecting breech – 65mm			
37. Portable foam injection and application system			
38. Hand controlled firefighting nozzle with building foam attachment			
39. Medium expansion Foam Branch with inline inductor and pick up tube			
40. 2400 L/M Oscillating Ground Monitor			
41. Class A Foam minimum 25liter			
42. Class B Foam minimum 25liter			
43. Emergency Light Set – Battery Operated – with 1,8m tripod stand to meet NFPA 1971-8, must be rechargeable with integrated rechargeable li-ion battery, waterproof and dustproof– IP-X7, must include AC & DC charging cords, must be supplied in moulded case.			
44. Wheeled generator 5.5kVa, Fuel type: Petrol, Manual/Electronic Ignition system			
45. 10 kg Sledgehammer			
46. 45cm PPV Fan – Dimensions - 6745MM X 554MM X 490MM with direct drive Petrol Motor			
47. Drip torch <ul style="list-style-type: none"> <li>• Tank- cold drawn steel welded 4.5 litres</li> <li>• Extension wand – steel tubing, steel nozzle</li> <li>• Burner- Fiberglass packed replaceable bolt on</li> </ul>			
48. DCP fire extinguisher (9kg)			
49. Co2 fire extinguisher (5kg)			
50. Foam fire extinguisher (9kg)			
51. DCP fire extinguisher (4.5kg)			
52. Extension ladder aluminium minimum 6meters extension			
53. Hydraulic rescue Cutter Heavy duty - battery operated: Batteries must be Lithium-ion type, 28V with high output with minimum 5,5Ah. The tool must be supplied with a battery and a 220V and 12/24V Vehicle Charger. I. Construction must be lightweight and slim			



<ul style="list-style-type: none"> <li>m. The rescue cutter must use smooth cut technology for smooth, low-stress and safe cutting</li> <li>n. The cutter blades must be high-strength, forged lightweight with optimised blade geometry for maximum safety with low weight</li> <li>o. It must have a handle manufactured from glass fibre reinforced plastic that can rotate 360° for use in tight spaces</li> <li>p. The rescue cutter must have blade inserts for blade protection and easy replacement</li> <li>q. The tool must have a maximum opening size of 187mm at the tips</li> <li>r. The tool must comply with EN Class BC187K-21,9</li> <li>s. The tool must comply with NFPA Class A8-B9-C7-D9-E9-F4</li> <li>t. EN cutting performance (EN 13204) 1K-2K-3K-4K-5K</li> <li>u. The tool with battery included must weigh maximum 19,1 kg</li> <li>v. Dimensions must not exceed: <ul style="list-style-type: none"> <li>1. Length: approximately 920mm</li> <li>2. Width: approximately 236mm</li> <li>3. Height: approximately 241 mm</li> </ul> </li> </ul>			
<p>54. Hydraulic Rescue Spreader Heavy duty - battery operated:  Batteries must be Lithium-ion type, 28V with high output with minimum 5,5Ah. The tool must be supplied with a battery and a 220V and 12/24V Vehicle Charger.</p> <ul style="list-style-type: none"> <li>j. Construction must be lightweight and slim</li> <li>k. Tips must have interior and exterior spikes for extra grip</li> <li>l. It must have a handle manufactured from glass fibre reinforced plastic that can rotate 360° for use in tight spaces</li> <li>m. It must have a spreading width of at least 805mm and a pulling width of at least 680mm</li> <li>n. Spreading force in the working area must be 50 - 501kN</li> </ul>			

<ul style="list-style-type: none"> <li>o. Maximum squeezing force must be at least 144kN and pulling force must be at least 67kN</li> <li>p. Must comply with EN Class BS50/805-20.9</li> <li>q. The tool with battery included must weigh maximum 20.9 kg</li> <li>r. Dimensions must not exceed: <ul style="list-style-type: none"> <li>4. Length: approximately 1015mm</li> <li>5. Width: approximately 282mm</li> <li>6. Height: approximately 241 mm</li> </ul> </li> </ul>			
<p>55. Telescopic Hydraulic Rescue Ram Heavy duty - battery operated: Batteries must be Lithium-ion type, 28V with high output with minimum 5,5Ah. The tool must be supplied with a battery and a 220V and 12/24V Vehicle Charger.</p> <ul style="list-style-type: none"> <li>j. Construction must be lightweight and slim</li> <li>k. The rescue ram must be telescopic with a maximum length of 1500mm</li> <li>l. The rescue ram must have integrated remaining length indication on the piston rod that must be easily visible</li> <li>m. The first stage pushing force must be maximum 108kN and the second stage pushing force must be maximum 62kN</li> <li>n. The closed length of the ram must be maximum 700mm and the extended length must be maximum 1500mm</li> <li>o. Must comply with EN Class: TR108/428-62/372-22,7-E-I</li> <li>p. Piston stroke for the first and second stages must be at least 428mm/372mm</li> <li>q. The tool with battery included must weigh maximum 22.7 kg</li> <li>r. Dimensions must not exceed: <ul style="list-style-type: none"> <li>7. Length closed: approximately 700mm</li> <li>8. Width : approximately 134mm</li> </ul> </li> </ul>			

9. Height: approximately 365 mm			
56. High lift jack (heavy duty) with minimum 3Ton Lifting Capacity			
57. 8 Bar Lifting Bag Set with Controllers: Set must consist of the following: 1 x 8 Bar Lifting bag – 230mm x 23mm x 25mm; Max lifting capacity of 2.7T; 1 x 8 Bar Lifting Bag – 380mm x 380mm x 25mm; Max Lifting capacity of 10.1T; 2 x * 8 Bar Flat Lifting Bags – 610mm x 610mm x 25mm – Max Lifting capacity of 25.2T; 1 x 200/300 Bar Pressure Reducer 2 x 25m inflation hose (1 x red & 1 x yellow) 1 x Double Controller			
58a. SCBA complete set <ul style="list-style-type: none"> <li>• FPS7000 mask</li> <li>• Steel cylinder</li> <li>• PSS4000 back plate</li> </ul>			
58b. SCBA complete set <ul style="list-style-type: none"> <li>• FPS7000 mask</li> <li>• Composite cylinder</li> <li>• PSS4000 back plate</li> </ul>			
59. Spare cylinder (300 bar) steel			
60. Spare cylinder (300 bar) composite			
61. Bakkie sakkie 600 litres plastic tank with steel frame <ul style="list-style-type: none"> <li>• FP60T GX 160 petrol</li> <li>• 20mm x 60 meter rubber hose</li> <li>• Adjustable nozzle</li> <li>Chains and adjustment</li> </ul>			
62. Stand pipe (aluminum) <ul style="list-style-type: none"> <li>• Inlet-bayonet connection (large)</li> <li>• Outlet – 65mm female</li> </ul>			
63. Stand pipe –(aluminum) <ul style="list-style-type: none"> <li>• Inlet-V –tred</li> <li>• Outlet- 65mm female</li> </ul>			
64. Hazmat plastic shovel			
65. Big bass broom <ul style="list-style-type: none"> <li>• Wooden handle</li> <li>• 1.2 meter</li> <li>• Broom width 0.6m</li> </ul>			
66. Heavy duty chain 20 meters			
67. Jerry can 10 liters metal			
68. Basket Stretcher aluminum /Stainless Steel with lifting bridles for helicopter rescue			
69. Car wash flexible hose <ul style="list-style-type: none"> <li>• Tap connector</li> <li>• Adjustable nozzle branch</li> <li>• 15mm x 30meters</li> </ul>			
70. Heavy duty electric extension cord <ul style="list-style-type: none"> <li>• With frame with 3x sockets (40 meters)</li> </ul>			

71. Jumper cables (heavy duty) min 3000amp capacity			
72. Scoop stretcher – Aluminum			
73. Sked stretcher			
74. Spinal board – Plastic with spider harness and head blocks			
75. SCBA compressor (electric) – 300 Bar			
76. Lawnmower minimum 190cc push petrol powered lawn mower, Cutting width: 48 cm, Minimum cutting height: 2 cm. minimum power: 3400 W, a powder coated steel chassis and heavy duty wheels for use in large gardens			
77. Fire beater: <ul style="list-style-type: none"> <li>• with wooden handle</li> <li>• 1.5m</li> <li>• with rubber flap</li> <li>• Length 0.9m, width 0.4m.</li> </ul>			
78. Squeege			
79. Crow bar minimum 750mm x 19mm			
80. Boboian wrench spanner minimum 30cm			
81. Fire drag rake – clawed with wooden handle			
82. Battery operated reciprocating saw with battery and charger in carry case			
83. Foil Mylar thermal blanket			
84. Pick up tube with inline inductor			
85. Knapsack backpack tank capacity 20liters			
86. Chisel 3 Piece Cold Chisel Set			
87. Folding ladder aluminum multipurpose minimum 3m extension			
<b>Sub-Total</b>			
<b>VAT@15%</b>			
<b>Total</b>			